

UNR521xG Series

Silicon NPN epitaxial planar type

For digital circuits

■ Features

- Costs can be reduced through downsizing of the equipment and reduction of the number of parts
- S-Mini type package, allowing automatic insertion through the tape packing and magazine packing


■ Resistance by Part Number

	Marking symbol	(R ₁)	(R ₂)
• UNR5210G	8L	47 kΩ	—
• UNR5211G	8A	10 kΩ	10 kΩ
• UNR5212G	8B	22 kΩ	22 kΩ
• UNR5213G	8C	47 kΩ	47 kΩ
• UNR5214G	8D	10 kΩ	47 kΩ
• UNR5215G	8E	10 kΩ	—
• UNR5216G	8F	4.7 kΩ	—
• UNR5217G	8H	22 kΩ	—
• UNR5218G	8I	0.51 kΩ	5.1 kΩ
• UNR5219G	8K	1 kΩ	10 kΩ
• UNR521DG	8M	47 kΩ	10 kΩ
• UNR521EG	8N	47 kΩ	22 kΩ
• UNR521FG	8O	4.7 kΩ	10 kΩ
• UNR521KG	8P	10 kΩ	4.7 kΩ
• UNR521LG	8Q	4.7 kΩ	4.7 kΩ
• UNR521MG	EL	2.2 kΩ	47 kΩ
• UNR521NG	EX	4.7 kΩ	47 kΩ
• UNR521TG	EZ	22 kΩ	47 kΩ
• UNR521VG	FD	2.2 kΩ	2.2 kΩ
• UNR521ZG	FF	4.7 kΩ	22 kΩ

■ Package

- Code
SMini3-F2
- Pin Name
1: Base
2: Emitter
3: Collector

■ Internal Connection



■ Absolute Maximum Ratings T_a = 25°C

Parameter	Symbol	Rating	Unit
Collector-base voltage (Emitter open)	V _{CBO}	50	V
Collector-emitter voltage (Base open)	V _{CEO}	50	V
Collector current	I _C	100	mA
Total power dissipation	P _T	150	mW
Junction temperature	T _j	150	°C
Storage temperature	T _{stg}	-55 to +150	°C

■ Electrical Characteristics $T_a = 25^\circ\text{C} \pm 3^\circ\text{C}$

Parameter		Symbol	Conditions	Min	Typ	Max	Unit
Collector-base voltage (Emitter open)		V_{CBO}	$I_C = 10 \mu\text{A}, I_E = 0$	50			V
Collector-emitter voltage (Base open)		V_{CEO}	$I_C = 2 \text{ mA}, I_B = 0$	50			V
Collector-base cutoff current (Emitter open)		I_{CBO}	$V_{CB} = 50 \text{ V}, I_E = 0$			0.1	μA
Collector-emitter cutoff current (Base open)		I_{CEO}	$V_{CE} = 50 \text{ V}, I_B = 0$			0.5	
Emitter-base cutoff current (Collector open)	UNR5210G/5215G/5216G/5217G	I_{EBO}	$V_{EB} = 6 \text{ V}, I_C = 0$			0.01	mA
	UNR5213G					0.1	
	UNR5212G/5214G/521DG/ 521EG/521MG/521NG/521TG					0.2	
	UNR521ZG					0.4	
	UNR5211G					0.5	
	UNR521FG/521KG					1.0	
	UNR5219G					1.5	
	UNR5218G/521LG/521VG					2.0	
Forward current transfer ratio	UNR521VG	h_{FE}	$V_{CE} = 10 \text{ V}, I_C = 5 \text{ mA}$	6		20	—
	UNR5218G/521KG/521LG			20			
	UNR5219G/521DG/521FG			30			
	UNR5211G			35			
	UNR5212G/521EG			60			
	UNR521ZG			60	200		
	UNR5213G/5214G/521MG			80			
	UNR521NG/521TG			80	400		
	UNR5210G*/5215G*/5216G*/5217G*			160	460		
Collector-emitter saturation voltage		$V_{CE(sat)}$	$I_C = 10 \text{ mA}, I_B = 0.3 \text{ mA}$			0.25	V
UNR521VG				$I_C = 10 \text{ mA}, I_B = 1.5 \text{ mA}$			
Output voltage high-level		V_{OH}	$V_{CC} = 5 \text{ V}, V_B = 0.5 \text{ V}, R_L = 1 \text{ k}\Omega$	4.9			V
Output voltage low-level		V_{OL}	$V_{CC} = 5 \text{ V}, V_B = 2.5 \text{ V}, R_L = 1 \text{ k}\Omega$			0.2	V
UNR5213G/521KG			$V_{CC} = 5 \text{ V}, V_B = 3.5 \text{ V}, R_L = 1 \text{ k}\Omega$				
UNR521DG			$V_{CC} = 5 \text{ V}, V_B = 10 \text{ V}, R_L = 1 \text{ k}\Omega$				
UNR521EG			$V_{CC} = 5 \text{ V}, V_B = 6.0 \text{ V}, R_L = 1 \text{ k}\Omega$				
Transition frequency		f_T	$V_{CB} = 10 \text{ V}, I_E = -2 \text{ mA}, f = 200 \text{ MHz}$		150		MHz
Input resistance	UNR5218G	R_1		-30%	0.51	+30%	k Ω
	UNR5219G				1.0		
	UNR521MG/521VG				2.2		
	UNR5216G/521FG/521LG/ 521NG/521ZG				4.7		
	UNR5211G/5214G/5215G/521KG				10		
	UNR5212G/5217G/521TG				22		
	UNR5210G/5213G/521DG/521EG				47		

Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7030 measuring methods for transistors.

2. *: Rank classification


Rank	Q	R	S	No-rank
h_{FE}	160 to 260	210 to 340	290 to 460	160 to 460

■ Electrical Characteristics (continued) $T_a = 25^\circ\text{C} \pm 3^\circ\text{C}$




	Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Resistance ratio	UNR521MG	R_1/R_2			0.047		—
	UNR521NG				0.1		
	UNR5218G/5219G			0.08	0.10	0.12	
	UNR521ZG				0.21		
	UNR5214G			0.17	0.21	0.25	
	UNR521TG				0.47		
	UNR521FG			0.37	0.47	0.57	
	UNR521VG				1.0		
	UNR5211G/5212G/5213G/5211LG			0.8	1.0	1.2	
	UNR521KG			1.70	2.13	2.60	
	UNR521EG			1.70	2.14	2.60	
	UNR521DG			3.7	4.7	5.7	




Note) Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7030 measuring methods for transistors.

Common characteristics chart









Characteristics charts of UNR5210G














Characteristics charts of UNR5211G






Characteristics charts of UNR5212G









Characteristics charts of UNR5213G














Characteristics charts of UNR5214G






Characteristics charts of UNR5215G









Characteristics charts of UNR5216G














Characteristics charts of UNR5217G






Characteristics charts of UNR5218G









Characteristics charts of UNR5219G














Characteristics charts of UNR521DG






Characteristics charts of UNR521EG








Characteristics charts of UNR521FG













Characteristics charts of UNR521KG






Characteristics charts of UNR521LG









Characteristics charts of UNR521MG














Characteristics charts of UNR521NG






Characteristics charts of UNR521TG









Characteristics charts of UNR521VG







Characteristics charts of UNR521ZG



SMini3-F2

Unit: mm



Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products, and no license is granted under any intellectual property right or other right owned by our company or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information described in this book.
- (3) The products described in this book are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
 - Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.