

# PIN RECEPTACLES

**FOR 0,38 - 0,51 DIAMETER PINS (#1 CONTACT)  
AND 0,38 - 0,56 DIAMETER PINS (#2 CONTACT)  
(SEE SPECIFIC CONTACT RANGE ON PAGE 251)**

<p><b>8467</b> <b>8467-0-15-XX-21-XX-04-0</b> Hex press-fit in 0,91 plated through-hole</p>	<p><b>6192</b> <b>6192-0-15-XX-21-XX-04-0</b> Square press-fit in 0,81 plated through-hole</p>	<p><b>9553</b> <b>9553-0-15-XX-X1-XX-04-0</b> Hex press-fit in 1,04 plated through-hole</p>	<p><b>5531</b> <b>5531-0-15-XX-21-XX-10-0</b> Hex press-fit in 1,04 plated through-hole</p>
<p><b>7553</b> <b>7553-0-15-XX-11-XX-10-0</b> Hex press-fit in 1,04 plated through-hole</p>	<p><b>9407</b> <b>9407-0-15-XX-11-XX-10-0</b> Solder mount in 1,02 min. mounting hole</p>	<p><b>9462</b> <b>9462-0-15-XX-21-XX-04-0</b> Hex press-fit in 1,09 plated through-hole</p>	<p><b>1147</b> <b>1147-0-18-XX-21-XX-10-0</b> Press-fit in 1,09 min. mounting hole Accepts wire sizes up to 0,36 dia.</p>
<p><b>3061</b> <b>3061-0-19-XX-21-XX-10-0</b> Wire Crimp Termination. Accepts wire sizes 28 AWG Max. / 32 AWG Min.</p>	<p><b>0579</b> <b>0579-0-15-XX-X1-XX-10-0</b> Press-fit in 1,02 mounting hole</p>	<p><b>8874</b> <b>8874-0-15-XX-11-XX-10-0</b> Bottom entry surface mount See page 152 for application details</p>	<p><b>0613</b> <b>0613-0-15-XX-21-XX-10-0</b> Press-fit in 1,19 mounting hole</p>

## SPECIFICATIONS:

**Shell Material:** Brass Alloy 360, 1/2 Hard

**Contact Material:** Beryllium Copper Alloy 172, HT

**Dimensions:** Millimeters

**Tolerances On:** Lengths: ± 0,13

Diameters: ± 0,051

Angles: ± 2°



**ORDER CODE: XXXX - X - 1X - XX - XX - XX - 0**

**BASIC PART #**

**SPECIFY SHELL FINISH:**

01 5,08µm TIN/LEAD OVER NICKEL

◆ 80 5,08µm TIN OVER NICKEL (RoHS)

◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**

02 2,54µm TIN/LEAD OVER NICKEL

◆ 84 2,54µm TIN OVER NICKEL (RoHS)

◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

**#11 or #21 CONTACT (DATA ON PAGE 251)**

(For alternate contact choices, see group A on page 248)

